



ÜNVER[®]
AĞAÇ İŞLEME MAKİNALARI
SINCE 1980



- TEMİZLEME SİSTEMİ MEKANİK TİTREŞİM MOTORU İLE ÇALIŞMAKTADIR.
- SİSTEMDE FİLTRE ÖMRÜNÜ UZATAN BASINÇ ODASI BULUNMAKTADIR.
- TEMİZLENEN HAVA ÜNİTE ÜZERİNDEKİ 500 MM ÇAPINDA TAZE HAVA ÇIKIŞ BACASI İLE TAHLİYE EDİLMEKTEDİR.
- SİSTEME BİRDEN FAZLA FAN BAĞLANMASI DURUMUNDA, BÜTÜN FAN-LARIN ÖNÜNE OTOMATİK AÇILIP KAPANABİLEN KLEPE KONMAKTADIR.
- BU SAYEDE ÇALIŞMAYAN FAN ÜZERİNDEN GELEN TOZUN GEÇİŞİ ENGEL-LENİR.
- ÖZEL BÜKÜMLÜ SACTAN İMAL EDİLMEKTEDİR.
- SAC BİRLEŞİMLERİNDE SU VE DIŞ ORTAM ETKİLERİNE KARŞI DAYANIKLI SIVI CONTA KULLANILMAKTADIR.
- ÜNİTELERDE KOLAY DEĞİŞTİRİLEBİLEN ÇİFT TARAFI ESNEK ÇEMBERLİ FİLTRE KULLANILMAKTADIR.
- ÜNİTELER İKİ RENK ELEKTROSTATİK TOZ BOYA İLE BOYANMAKTADIR.

TORBALI FİLTRELEME ÜNİTELERİ FILTRATION UNITS WITH PVC BAG

- THE CLEANING SYSTEM WORKS WITH A MECHANICAL VIBRATION MOTOR.
- THE SYSTEM HAS A PRESSURE ROOM THAT PROLONGS THE FILTER LIFE.
- THE CLEANED AIR IS DISCHARGED WITH A FRESH AIR OUTLET WITH DIAMETER OF 500 MM ON THE UNIT.
- IF MORE THAN ONE FAN IS CONNECTED TO THE SYSTEM, A CLACK THAT CAN BE OPENED AND CLOSED AUTOMATICALLY IS PLACED IN FRONT OF ALL FANS.
- IN THIS WAY, THE PASSAGE OF DUST COMING FROM THE NON-WORKING FAN IS PREVENTED.
- IT IS MANUFACTURED FROM SPECIAL BENDED SHEET METAL.
- IN THE SHEET METAL JOINTS, LIQUID GASKETS RESISTANT TO WATER AND OUTDOOR EFFECTS ARE USED.
- DOUBLE-SIDED FLEXIBLE RING FILTER IS USED IN THE UNITS, WHICH CAN BE EASILY CHANGED.
- UNITS ARE PAINTED WITH TWO COLORS ELECTROSTATIC POWDER PAINT.

TEKNİK ÖZELLİKLER / TECHNICAL INFORMATIONS

FİLTRELEME KAPASİTESİ / FILTRATION CAPACITY	8.000 M3/H	10.000 M3/H	12.000 M3/H	16.000 M3/H	20.000 M3/H	24.000 M3/H
KURULU ÜNİTE EBATLARI (EN X BOY X YÜKSEKLİK) / UNIT SIZES (WIDTH X HEIGHT X LENGTH)	1.7X2.6X3.1M	1.7X3.5X3.1M	1.7X3.36X3.1M	1.7X3.36X3.6M	1.7X4.18X3.6M	1.7X5X3.6M
ATIK BOŞALTMA SİSTEMİ / UNLOADING TYPE	Ø600 6 ADET PVC TORBA (6 PIECES PVC BAG)	Ø600 6 ADET PVC TORBA (6 PIECES PVC BAG)	Ø600 8 ADET PVC TORBA (8 PIECES PVC BAG)	Ø600 8 ADET PVC TORBA (8 PIECES PVC BAG)	Ø600 10 ADET PVC TORBA (10 PIECES PVC BAG)	Ø600 12 ADET PVC TORBA (12 PIECES PVC BAG)
ATIK DEPOLAMA KAPASİTESİ / UNLOADING CAPACITY	1,68 M3	1,68 M3	2,24 M3	2,24 M3	2,8 M3	3,36 M3
TİTREŞİM MOTORU / VIBRATION MOTOR	0.16 KW 1400 DD	0.16 KW 1400 DD	0.16 KW 1400 DD	0.16 KW 1400 DD	0.16 KW 1400 DD	0.16 KW 1400 DD
TİTREŞİM MOTOR ADETİ / VIBRATION MOTOR QUANTITY	1 ADET / PIECE	1 ADET / PIECE	1 ADET / PIECE	1 ADET / PIECE	1 ADET / PIECE	1 ADET / PIECE
FİLTRE ADETİ / FILTER QUANTITY	72 ADET / PIECE	72 ADET / PIECE	96 ADET / PIECE	96 ADET / PIECE	120 ADET / PIECE	144 ADET / PIECE
FİLTRE ÖLÇÜLERİ / FILTER SIZES	Q160X1380 MM	Q160X1380 MM	Q160X1380 MM	Q160X1780 MM	Q160X1780 MM	Q160X1780 MM
FİLTRE YÜZEY ALANI / FILTER SURFACE AREA	49,91 M2	49,91 M2	66,55 M2	85,85 M2	107,31 M2	128,77 M2
FİLTRE GEÇİRGENLİĞİ / FILTER PERMEABILITY	0,5 MİCRON	0,5 MİCRON	0,5 MİCRON	0,5 MİCRON	0,5 MİCRON	0,5 MİCRON

MAĞAZA / SHOWROOM

Önder Mah. Akçeşme Sok. No: 14
Siteler / Altındağ / ANKARA / TURKEY
Tel: +90 312 349 68 68 - 69
Fax: +90 312 351 80 80

FABRİKA / FACTORY

Önder Mah. Akçakale 2 Cadde No: 95
Siteler / ANKARA / TURKEY
Tel: +90 312 815 15 58
Fax: +90 312 815 15 59



www.unvermakina.com.tr | unvermakina@unvermakina.com.tr

www.instagram.com/unver_makina | www.facebook.com/unvermakina